

PRODUCT DATA

Product: PP SHEET (NORMAL)

Description:	- PP (Polypropylene) Sheet - Silicone Free or Silicone coated
--------------	--

Application:	- Suitable for vacuum forming and thermoforming. - Widely used in food and electronic packaging.
--------------	---

Melt Index (MI):	~0.50 g/10min
Standard: ASTM D-1238	(Test condition: 230°C x 2.16kg)

Specific Gravity:	0.90
-------------------	------

Molding Shrinkage:	1.5 ~ 1.9 %
--------------------	-------------

Tensile Strength @ Yield:	360 kg/cm ²
Standard: ASTM D-638	

Elongation @ Break:	> 200%
Standard: ASTM D-638	

Thickness Range:	0.20 – 1.00 mm
------------------	----------------

Width Range:	450 – 700 mm
--------------	--------------

Packaging:	50 – 100 kg/roll
Storage:	The product should stored in a cool and dry place
Compliance declaration:	Please contact us for details (Food contact, Silicone free...)

The above information is based on the present state of our knowledge and is intended to describe our products and their possible application. The user must make his own responsibilities of its suitability and completeness for the specific use, for the protection of environment, and for the health and safety of his employees and purchasers of his products. Any existing industrial rights are to be taken into consideration. Quality is guaranteed in accordance with our general conditions of sale.

Chansin Co., Ltd.

B8/35B Duong Hung Nhon, Xa Tan Kien,
Huyen Binh Chanh, Ho Chi Minh City, Vietnam
Tel: +84-83-9606394 – 8587063

Fax: +84-83-9634597

GREAT ALLIANCE TRADING (SINGAPORE) PTE LTD
Co Reg No: 200705352N
33 Ubi Ave 3 Vertex # 04 -27
Singapore 408868
Tel: (65) 6224 9770 Fax: (65) 6220 5131

Page: 1/1
Printed: 05.12.13